



TWM-606 整流子自動開槽機 Automatic Commutator Slotting Machine

適合各式碳刷,串激類馬達整流子之自動開槽作業
It is applicable to automatic commutator slotting for a variety of carbon brush and series motors.



機台功能規格書 MACHINE SPECIFICATIONS

電力需求	Power supply	220V(380V)
空(油)壓力	Pneumatic (hydraulic) supply	5kg/cm ²
轉子外徑	Armature external diameter	φ 40mm-55mm
整流子外徑	Commutator external diameter	φ 20mm-45mm
轉子總長度	Armature length	<250mm
機台淨重	Machine net weight	350kg
機台尺寸	Machine size	1000(D)700(W)1600(H)mm
作業精度	Working precision	±0.2°
切削單元	Slotting Unit	雙軸同步切削Twin Spindle Synchronization Slotting
轉子移位裝置	Armature Positioning Device	伺服控制移位 Servo Control System
切削進給單元	Cutting Feed Device	伺服控制獨立進給 Biaxial Servo Controlled Independently Feed
控制系統	Control System	日系三菱PLC模組 Japanese-mitsubish series PLC
工作參數記憶	Parameter Memory	標準配備 Standard moudule
快速換模	Quick Die Change	標準配備 Standard moudule
異常偵測系統	Error Detection & Display System	標準配備 Standard moudule
主動式保養提示	Service Prompt	標準配備 Standard moudule
機械手臂與輸送帶連結功能	Robot Manipulator & Conveyor Connection	選擇配備 Optional moudule
手輪動態模擬系統	Manual Pulse Generator System	選擇配備 Optional moudule
遠距程式監控維護	Distant Programming Monitoring System	標準配備 Standard moudule

• 若您所需求之規格不在上述範圍內,請與協群聯絡,我們保有在未獲通知的情況下作技術修改的權利。

Please contact TeamWork for requirements outside these specifications.

We reserve the right of technical modifications without notice.

