



TWM-702 嵌入式轉子自動繞線機

Automatic Stuff Type Armature Winding Machine

適合各式碳刷、串激類馬達轉子自動捲線

It is applicable to armatures automatic winding for a variety of carbon brush and series motors.



機台功能規格書 MACHINE SPECIFICATIONS

電力需求	Power supply	220V(380V)	
空(油)壓力	Pneumatic (hydraulic) supply	5kg/cm ²	
轉子外徑	Armature external diameter(max)	φ 25mm-55mm(type1)	φ 50mm-85mm(type2)
整流子外徑	Commutator external diameter	φ 25mm-40mm(type1)	φ 35mm-55mm(type2)
轉子積厚	Core thickness	φ 25mm-70mm(type1)	φ 35mm-100mm(type2)
適用線徑	Applicable wire diameter	0.4mm-1.0mm	
繞線速度	Winding speed(max)	2000rpm(Depending on winding item)	
機台淨重	Machine net weight	1300kg	
機台尺寸	Machine size	2210(D)2000(W)1970(H)mm	
捲線機構	Coil Winding Unit	2組伺服控制 Servo Control X 2 Set	
轉子移位裝置	Armature Positioning Device	1組伺服控制 Servo Control X 1 Set	
張力系統	Tension Device	Type1: 類比式控制 Analog Tension Output Control	
		Type2: 2組伺服控制 Servo Control & D/A X 2 Set	
控制系統	Control System	日系三菱PLC模組 Japanese-mitsubish series PLC	
工作參數記憶	Parameter Memory	標準配備 Standard module	
快速換模	Quick Die Change	標準配備 Standard module	
異常偵測系統	Error Detection & Display System	標準配備 Standard module	
主動式保養提示	Service Prompt	標準配備 Standard module	
機械手臂與輸送帶連結功能	Robot Manipulator & Conveyor Connection	選擇配備 Optional module	
遠距程式監控維護	Distant Programming Monitoring System	標準配備 Standard module	

• 若您所需求之規格不在上述範圍內，請與協群聯絡，我們保有在未獲通知的情況下作技術修改的權利。
Please contact TeamWork for requirements outside these specifications.
We reserve the right of technical modifications without notice.

